



RAVENOL ATF FZ

RAVENOL ATF FZ is a fully synthetic ATF with low viscosity with special additives and inhibition which guarantees a perfect function of the automatic transmission.

RAVENOL ATF FZ is a Full Synth. Low Viscosity ATF (Automatic Transmission Fluid) especially for Mazda 6-Stroke transmission FW6A-EL und FW6AX-EL with SKYACTIV technology. It guarantees in any mode for maximum wear protection.

Application Notes

RAVENOL ATF FZ is for use in special automatic transmission of Mazda 6-Stroke transmission FW6A-EL und FW6AX-EL with SKYACTIV technology.

Quality Classifications

Practice and tested in aggregates with filling

Mazda ATF FZ, Mazda 0000-FZ-113E-01, Mazda 8300-77-246

Characteristic

RAVENOL ATF FZ offers:

- Very good lubricating ability even at low temperatures in winter
 - A high, stable viscosity index
 - Very good oxidation stability
 - Protection against corrosion and foam formation
 - Good balanced coefficient of friction
 - A high thermal and oxidative stability
 - An excellent cooling capacity.
- RAVENOL special transmission fluid is special development for special gear and cannot be selected on the basis of technical parameters (viscosity, etc.). Therefore the decision was made not to give technical data.
 - **Please note:** RAVENOL special transmission fluid is exclusively to apply under the original number, as indicated in the product information. Not sure of the correct transmission fluid, you can ask your garage or the car dealer with respect to the original OEM gear type and number or consult our advisers. It must be specified the VIN code (Vehicle Identification Number) of your vehicle.
 - Misapplication of RAVENOL special transmission fluid can lead to malfunction of the transmission shifting problems, increased fuel consumption, unwanted slip behavior, etc. cause and cause the failure of the transmission.
 - Ravensberger Schmierstoffvertrieb GmbH does not liable for transmission failures in case of wrong selection of RAVENOL special transmission fluid.

Characteristics	Unit	Data	Audit
Colour		blue	visual
Density at 20°C	kg/m³	837	EN ISO 12185
Pourpoint	°C	<-50	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

04.11.2015

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41