



RAVENOL DCT/DSG Getriebe Fluid

RAVENOL DCT/DSG Getriebe Fluid is semi synthetic gear oil for Dual Clutch Gear DCG.

RAVENOL DCT/DSG Getriebe Fluid guarantees good lubricating properties even at extremely temperatures in summer and low winter temperatures.

RAVENOL DCT/DSG Getriebe Fluid allows virtually slip-free operation and thus minimal torque losses. Ensures low wear and long life of the transmission. Fuel economy.

Application Notes:

RAVENOL DCT/DSG Getriebe Fluid has been developed especially for Dual Clutch Gear of several manufacturers like VW/Audi, Ford, Volvo, Chrysler, Dodge, Mitsubishi and others.

RAVENOL DCT/DSG Getriebe Fluid is also recommended for use in Dual Clutch Gear DQ-250 (02E) and DQ-500 (0BT) acc. to VW Part-No. G 052 182 and DL-501 (0B5) acc. to VW Part-No. G 052 529 for S-Tronic of VW, Audi, Seat and Skoda.

Quality Classifications:

RAVENOL DCT/DSG Getriebe Fluid is tried and tested for aggregates specifying:

Practice and tested in aggregates with filling:

VW G 052 182 A2, Audi G 052 529 A2 S-Tronic, BMW DCTF-1, BMW 83220440214, 83222148579, 83222148578, 83222147477, FORD 1490763, FORD 1490761, FORD WSS-M2C936-A, FORD USA XT-11-QDC, FORD WSD-M2C200-D2, Chrysler 68044345 EA, Peugeot/Citroën 9734.S2 for DCS6 (Peugeot 4007, CITROËN C-CROSSER), FIAT 9.55550-MZ6 für TCT (Twin Clutch Transmission) in Alfa Romeo MiTo und Giulietta, Renault EDC (Efficiency Dual Clutch System), VOLVO 1161838, VOLVO 1161839, MITSUBISHI MZ320065, MITSUBISHI Dia-Queen SSTF-I, BOT 341, MB 236.21, Porsche 0000 043 20

Characteristics:

RAVENOL DCT/DSG Getriebe Fluid offers:

- Good lubricating properties also at low temperatures in winter
- Stable lubricant film even under extreme loads in summer
- Low wear
- Excellent viscosity-temperature behavior
- Very low pour point
- Low foaming even under heavy demands
- Extensive protection against wear, corrosion and foaming
- Neutral behavior towards sealing materials

RAVENOL special fluid is special development for special units and cannot be selected on the basis of technical parameters (viscosity, etc.). Therefore the decision was made not to give technical data.

Please note: RAVENOL special fluid is exclusively to apply under the original number, as indicated in the product information. Not sure of the correct fluid, you can ask your garage or the car dealer with respect to the original OEM type and number or consult our advisers. It must be specified the VIN code (Vehicle Identification Number) of your vehicle.

Misapplication of RAVENOL special fluid can lead to malfunction of the unit and cause failure.

Ravensberger Schmierstoffvertrieb GmbH does not liable for failures in case of wrong selection of RAVENOL special fluid.

Characteristics	Unit	Data	Audit
Colour		brown	visual
Density at 20°C	kg/m ³	837	EN ISO 12185
Pourpoint	°C	-45	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

02.03.2015

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41