



RAVENOL Feinmechaniköl

RAVENOL Feinmechaniköl is a multi-purpose, universal mechanics oil which is formulated to be resin and acid -free.

Application Notes

RAVENOL Feinmechaniköl can be used as a universal general purpose oil both in the home and out for bicycles, sewing machines, household and office equipment, locks, tools, cars, motorcycles, hobby work etc. and anywhere that this type of multi-purpose oil is required.

Characteristic

RAVENOL Feinmechaniköl is characterized by its light color, mild odor and a low sulphur content, making it pleasant in use. It is formulated to offer a long-lasting effect with little or no aging effect, and has a good viscosity-temperature behaviour making it suitable for use across a wide temperature range.

Characteristics	Unit	Data	Audit
Colour		hell	visual
Density at 15°C	kg/m ³	0,857	EN ISO 12185
Viscosity at 40°C	mm ² /s	14-17	DIN 51 562
Viscosity index VI		100	DIN ISO 2909
Flash point (COC)	°C	180	DIN ISO 2592
Pourpoint	°C	-12	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

14.05.2015

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41