

# **RAVENOL Formel Super SAE 15W-40**

RAVENOL Formel Super 15W-40 is high quality multi-grade engine oil which corresponds to all requirements of modern carburetor and Diesel engines. It can be used in passenger cars as well as trucks. It fulfils the requirements of modern Diesel engines with or without supercharging. The favourable viscosity area ensures a high lubrication capacity all the year under different operation circumstances.

## **Application Notes**

RAVENOL Formel Super 15W-40 can be used according to the manufacturer specification for Diesel as well as Otto engines.

## **Quality Classifications**

RAVENOL Formel Super 15W-40 is tried and tested for aggregates specifying:

#### **Specifications**

API SF/CD, ACEA A2/B2

## Practice and tested in aggregates with filling

MB-227.1, MIL-L-46152 B, MIL-L-2104 D, CCMC G4 (gültig bis 31.12.96)

### Characteristic

## RAVENOL Formel Super 15W-40 offers:

- Protection against corrosion
- A very good shear stability
- A very high oxidation stability
- An excellent viscosity temperature behaviour
- Efficient function of hydraulic shock absorbers (hydraulic valve compensation)
- Convincing detergent and dispersant attributes
- High security reserves even under limited lubrication conditions
- Neutrality against sealing materials
- Very good cold start attributes
- Avoids the formation of conglutinations, pigmenting, coking and accumulation of mud (black studge) on cylinders, pistons, valves, sparking plugs and in turbo superchargers
- No problems with the use in catalyst vehicles

Unit	Data	Audit
	yellow brown	visual
kg/m³	879	EN ISO 12185
mm²/s	100,6	DIN 51 562
mm²/s	13,6	DIN 51 562
	136	DIN ISO 2909
°C	223	DIN ISO 2592
°C	-27	DIN ISO 3016
mg KOH/g	6,0-9,0	DIN ISO 3771
%wt.	ca. 0,8	DIN 51 575
	kg/m³ mm²/s mm²/s °C °C mg KOH/g	kg/m³ yellow brown kg/m³ 879 mm²/s 100,6 mm²/s 13,6 136 °C 223 °C -27 mg KOH/g 6,0-9,0

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

05.10.2015

Ravensberger Schmierstoffvertrieb GmbH Postfach 1163

33819 Werther Tel.: 05203/9719-0 Fax.: 052039719-40 / 41