



RAVENOL Gasmotorenöl SAE 40

RAVENOL Gasmotorenöl SAE 40 is gas engine oil suitable for the lubrication of four stroke gas engines, when gases are used with lower sulphur contents.

Application Notes

RAVENOL Gasmotorenöl SAE 40 is suitable to apply in four stroke gas engines for which lower acid neutralisation capacity is required.

RAVENOL Gasmotorenöl SAE 40 can be applied when natural gas, biomass gas or sewage gas are used. Application of this motor oil contributes to a longer lifetime and decreased maintenance costs, because longer service fill times are possible. Due to its lower phosphate content a longer lifetime of the catalyst can be achieved.

Quality Classifications

Characteristic

RAVENOL Gasmotorenöl SAE 40 offers:

- Reduction of deposits in the combustion chamber and on the valves
- Good noise reducing properties
- Good oxidation resistance
- Strong acid neutralisation capacity
- Excellent cleaning properties
- Good protection against wear
- Excellent filterability

Characteristics	Unit	Data	Audit
Colour		brown	visual
Density at 20°C	kg/m ³	885	EN ISO 12185
Viscosity at 40°C	mm ² /s	143,00	DIN 51 562
Viscosity at 100°C	mm ² /s	14,7	DIN 51 562
Viscosity index VI		102	DIN ISO 2909
Flash point (COC)	°C	254	DIN ISO 2592
Pourpoint	°C	- 21	DIN ISO 3016
Base number	mgKOH/g	5,5	DIN ISO 3771
Acid number	mg KOH/g	1,84	-
Sulphated ash	%wt.	0,45	DIN 51 575

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

20.10.2015

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 05203/9719-40 / 41