

RAVENOL Getriebeöl CLP 150

RAVENOL Getriebeoel CLP 150 is a high quality, mineral-based gear oil formulated with lead-free high-pressure additives (EP additives). Its special active substance combination provides a good, stable high-pressure impact load capacity. RAVENOL Getriebeoel CLP 150 has a low pour point and therefore a very good cold behaviour.

Application Notes

RAVENOL Getriebeoel CLP 150 can be used as a lubricant in nearly all industrial gear drives due to its good stress and/or impact characteristics.

Quality Classifications:

RAVENOL Getriebeoel CLP 150 is tried and tested for aggregates specifying:

Specifications:

FZG 12, DIN 51 517 Part 3, US Steel 224

Characteristics:

RAVENOL Getriebeöl CLP 150 RAVENOL Gear Oil CLP 150 offers:

- A very good, stable high-pressure impact capacity.
- Resistant characteristics at high temperatures.
- A good rust and corrosion impeding effect.
- Excellent wear protection.
- Very good anti-foaming characteristics.
- A low pour point.
- Very good cold behaviour.

Characteristics	Unit	Data	Audit	
Colour		braun	visual	
Density at 20°C	kg/m³	892	EN ISO 12185	
Viscosity at 40°C	mm²/s	149,0	DIN 51 562	
Viscosity at 150°C	mm²/s	14,6	DIN 51 562	
Viscosity index VI		97	DIN ISO 2909	
Flash point (COC)	°C	225	DIN ISO 2592	
Pourpoint	°C	-24	DIN ISO 3016	

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

03.03.2015

Ravensberger Schmierstoffvertrieb GmbH Postfach 1163 33819 Werther

Tel.: 05203/9719-0 Fax.: 052039719-40 / 41