



RAVENOL Getriebeöl PSA SAE 75W-80

RAVENOL GETRIEBEÖL PSA SAE 75W-80 is a high-quality solvent refined base oil based semi-synthetic multi-grade transmission oil with special EP (extreme pressure) properties. RAVENOL GETRIEBEÖL PSA SAE 75W-80 has a special formula for outstanding wear protection and lubrication properties.

Application Notes

RAVENOL GETRIEBEÖL PSA SAE 75W-80 is used in manual shift transmissions requiring trouble-free lubrication. RAVENOL GETRIEBEÖL PSA SAE 75W-80 can be used in manual transmissions where the manufacturer specifies a low-viscosity oil.

Quality Classifications

Specifications

API GL-4 +

Practice and tested in aggregates with filling

PSA Standard B 71 2315

Characteristic

RAVENOL GETRIEBEÖL PSA SAE 75W-80 offers:

- Outstanding oxidation protection
- Low viscosity in low temperatures
- Excellent wear protection
- Enhanced EP properties
- Good foaming properties
- Neutral to sealants
- Outstanding protection from rust and corrosion

Characteristics	Unit	Data	Audit
Colour		brown	visual
Density at 20°C	kg/m ³	847	EN ISO 12185
Viscosity at 40°C	mm ² /s	52,8	DIN 51 562
Viscosity at 100°C	mm ² /s	8,9	DIN 51 562
Viscosity index VI		148	DIN ISO 2909
Flash point (COC)	°C	242	DIN ISO 2592
Pourpoint	°C	-36	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

03.11.2015

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41