



RAVENOL HTC - Protect MB325.0 Concentrate

AMINE - PHOSPHATE - FREE

RAVENOL HTC Hybrid Technology Coolant Concentrate is an all-season amine and phosphate-free mono-ethylene glycol based coolant with frost and rust protection for Mercedes, BMW, Opel, Saab and General Motors engines. This product is formulated based on a proven inhibitor development by combining silicates with the organic additive technology OAT as an extended life coolant.

The quality of an antifreeze is no longer just determined by the antifreeze effect (which automatically exists in an ethylene-glycol based product), but by the rust protection.

That is why automakers subject antifreeze to lengthy corrosion and cavitation tests.

RAVENOL HTC Hybrid Technology Coolant Concentrate protects the cooling system from rust, frost, and in summer, from overheating.

Application Notes

RAVENOL HTC Hybrid Technology Coolant Concentrate with frost and rust protection for year-round use in automotive engines.

Mix according to chart. Please follow manufacturer instructions.

Instructions: Clean cooling system, test leak tightness, flush.

Mix **RAVENOL HTC Hybrid Technology Coolant Concentrate** with clean water (per mixing chart) and add. Allow engine and heater to warm up, add coolant to fill level.

Quality Classifications

RAVENOL HTC Hybrid Technology Coolant Concentrate is tried and tested for aggregates specifying:

Specifications

ASTM D 3306, ASTM D 4985, ASTM D 4340, SAE J1034, NATO S-759, FORD ESE-M978B4H-A, FORD AF Plus, MAN 324, SAAB, GM 1825M, OPEL-GM QL130100, DAF, GM 1899M, GM 93740141, GM 93740140, MB A000989082510, VW-AUDI-PORSCHE, GM SATURN, ROVER, PORSCHE, John Deer, JAGUAR, BMW 81 22 9 407 454, 83 19 2 211 191, RENAULT, Honda OL999-9011

Approvals

MB 325.0, VW TL 774-C

Characteristic

RAVENOL HTC Hybrid Technology Coolant Concentrate offers:

- Excellent for use in cast iron or aluminium engines, or alloys of the two metals, and aluminium and copper alloy radiators
- Good reserve alkalinity
- Protection from corrosion and cavitation
- Prevents sediments and foaming in the cooling system
- Compatible with elastomers used in automotive radiators

Characteristics	Unit	Data	Audit
Colour		blau	visual
Density at 20°C	kg/m³	1130	EN ISO 12185
Flash point	°C	>100	DIN 51 758
Boiling point	°C	>160	ASTM D 1120
pH-value (50 %, 20°C)		7,5	ASTM D 1287
Reserve alkalinity	ml 0,1 n HCL	>15	ASTM D 1121
Water content	Gew.-%	<5	ASTM D 1123
Freezing point (50 %-Lösung)	°C	-37	ASTM D 1177

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

27.05.2015

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41