



## RAVENOL LHM+ Fluid

RAVENOL LHM+ FLUID is special semisynthetic hydraulic fluid especially designed for use in vehicles of the PSA group (Citroen, Peugeot). Due to its special formulation RAVENOL+ LHM FLUID has significantly improved low temperature viscosity and fulfils the PSA approval specification.

### Application Notes:

RAVENOL LHM+ FLUID is used in vehicles with appropriately marked fluid reservoir for the hydraulic operation or support of braking, steering and suspension functions. RAVENOL + LHM FLUID is miscible with earlier LHM fluids.

### Quality Classifications:

#### **Specifications:**

ISO 7308, DIN 51 524, Part 2

#### **Practice and tested in aggregates with filling:**

PSA B71 2710

### Characteristics:

RAVENOL LHM+ FLUID offers:

- A low pour point.
- Excellent viscosity behavior at low temperatures.
- An extremely high viscosity index.
- Low viscosity at low temperatures.
- Neutral behavior towards sealing materials.

Characteristics	Unit	Data	Audit
Colour		Klar, grün	visual
Density at 20°C	kg/m <sup>3</sup>	869	EN ISO 12185
Viscosity at 40°C	mm <sup>2</sup> /s	19,5	DIN 51 562
Viscosity at 100°C	mm <sup>2</sup> /s	6,5	DIN 51 562
Viscosity index VI		>280	DIN ISO 2909
Flash point (COC)	°C	>100	DIN ISO 2592
Pourpoint	°C	-50	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

03.03.2015

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41