



RAVENOL ODL 32 Druckluftöl

RAVENOL ODL 32 Druckluftöl is a special-compressed-air-oil for pneumatic tools of all systems.

RAVENOL ODL 32 Druckluftöl bonds condensed water, has an excellent corrosion protection, wear protection and an extraordinary pressure absorption capacity, a good adhesive power and high aging resistance. Easily conveying- and spray ability, economy consumption. No deposits caused by cleaning effects. Full power of impact.

Application Notes

RAVENOL ODL 32 Druckluftöl is specially suitable for pneumatic tools with sound-absorbing-case, for lubrication of rock drills, road breaker, chipping hammer and spade hammer, ram machines and other pneumatic aggregates. Application by pre-switch-lubricator according to working instructions or usable directly in the air pipe. Mind the manufacturer's instructions.

Quality Classifications

RAVENOL ODL 32 is tried and tested for aggregates specifying:

Practice and tested in aggregates with filling

ATLAS COPCO, Festo, Hilti, Bosch, Makita, Black&Decker, Cress, Ryobi, DeWalt, Sumake, Seno, Hitachi

Characteristic

RAVENOL ODL 32 offers:

- a high performance level
- a very good viscosity temperature behaviour
- a good adherence
- a high aging resistance
- a reliable wear protection
- an excellent corrosion protection
- neutrality of sealing materials

Characteristics	Unit	Data	Audit
Colour		gelbbraun	visual
Density at 20°C	kg/m ³	878	EN ISO 12185
Viscosity at 40°C	mm ² /s	32,7	DIN 51 562
Viscosity at 100°C	mm ² /s	5,4	DIN 51 562
Viscosity index VI		98	DIN ISO 2909
Flash point (COC)	°C	220	DIN ISO 2592
Pourpoint	°C	-24	DIN ISO 3016
FZG-Test A/8,3/90 damage loading step		12	DIN 51 354

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

05.06.2015

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41