



## RAVENOL RSS SAE 10W60

### RACING

RAVENOL RSS SAE 10W60 is high alloyed fully synthetic multigrade engine oil for modern gasoline engines based on esters and poly-alpha olefins.

Special oil for use by car race, even under the heaviest loads. Its high viscosity index, its good shear stability and a highly effective special additive RAVENOL RSS SAE 10W60 is suitable for extremely sporty driving style. Secure lubrication, even at very high operating temperatures. Excellent protection against wear, corrosion and foam.

### Application Notes

RAVENOL RSS SAE 10W60 can be used as special oil for car race even under most difficult conditions.

### Quality Classifications

RAVENOL RSS SAE 10W60 is tried and tested for aggregates specifying:

#### Specifications

API SN/CF, ACEA A3/B4

#### Practice and tested in aggregates with filling

MB 229.1

### Characteristic

RAVENOL RSS SAE 10W60 offers:

- Fuel saving regarding partial load operation and full power operation
- Very stable and excellent viscosity behaviour
- Very good cold start characteristics
- Safe lubricating layer at very high operating temperatures
- Very good detergent and dispersant characteristics
- Good protection against corrosion and foam formation

Characteristics	Unit	Data	Audit
Colour		braun	visual
Density at 20°C	kg/m³	850	EN ISO 12185
Viscosity at -25°C	mPa.s	5790	ASTM D5293
Viscosity at 40°C	mm²/s	155,59	DIN 51 562
Viscosity at 100°C	mm²/s	22,11	DIN 51 562
Viscosity index VI		169	DIN ISO 2909
Flash point (COC)	°C	236	DIN ISO 2592
Pourpoint	°C	- 36	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

29.10.2015

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41