

RAVENOL SCOOTER 2-Takt Mineral

RAVENOL SCOOTER 2-Takt Mineral is high quality mineral two-stroke engine oil.

RAVENOL SCOOTER 2-Takt Mineral is formulated with mineral base oils with effectively additives for optimum protection against wear and prevent corrosion, deposits and auto-ignitions. RAVENOL SCOOTER 2-Takt Mineral is optimized for air- and watercooled two stroke engines.

Application Notes

RAVENOL SCOOTER 2-Takt Mineral can generally be mixed with regular petrol 1:50.

RAVENOL SCOOTER 2-Takt Mineral is best choice for separate lubrication and self-mixing systems. The use in oil injection systems this product will ensure optimum lubrication and minimizes smoke environmentally friendly.

RAVENOL SCOOTER 2-Takt Mineral is used for lubrication of air-cooled two-stroke petrol engines.

RAVENOL SCOOTER 2-Takt Mineral is also suitable for the lubrication of two stroke scooters with water cooling. Suitable for separate lubrication systems and self-mixing systems.

Quality Classifications

RAVENOL SCOOTER 2-Takt Mineral corresponds to and fulfils following specification:

Specifications

API TB, ISO-L-EGB

Approvals

JASO 049RAV156

Practice and tested in aggregates with filling

Aprilia, Honda, Suzuki, Yamaha, JASO FB, Kymco, Peugeot, Piaggio, Vespa

Characteristic

RAVENOL SCOOTER 2-Takt Mineral offers:

- · A proper lubrication of all engine parts
- · A strong cleaning effect, for clean combustion chambers. Cleans intake and exhaust ports from combustion residues and deposits
- · Clean spark plugs provide optimal performance of the engines
- · A very high wear and corrosion protection
- · Low exhaust emission levels by good combustion

| Characteristics | Unit | Data | Audit |
|--------------------|-------|-------|--------------|
| Colour | | rot | visual |
| Density at 20°C | kg/m³ | 0,872 | EN ISO 12185 |
| Viscosity at 40°C | mm²/s | 70,0 | DIN 51 562 |
| Viscosity at 100°C | mm²/s | 9,7 | DIN 51 562 |
| Viscosity index VI | | 118 | DIN ISO 2909 |
| Pourpoint | °C | -24 | DIN ISO 3016 |

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

21.10.2015

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163 33819 Werther Tel.: 05203/9719-0 Fax.: 052039719-40 / 41