



RAVENOL SU5 ATF Fluid

ATF Professional Line

RAVENOL SU5 ATF Fluid is fully synthetic ATF based on PAO with special additives and inhibition, which ensure the proper function of automatic transmission.

RAVENOL SU5 ATF Fluid is specially developed ATF (Automatic-Transmission-Fluid) for the latest Subaru automatic transmissions. It guarantees a high wear protection in all operating conditions.

RAVENOL SU5 ATF Fluid has red colour.

Application Notes

RAVENOL SU5 ATF Fluid is suitable for use in five-speed automatic transmissions of Subaru.

Quality Classifications

RAVENOL SU5 ATF Fluid is tried and tested for aggregates specifying:

Practice and tested in aggregates with filling

Subaru 4ATF, 5ATF, ATF HP, Subaru K0415-Y0700, Subaru SOA868V940, SOA868V9241, SOA427V1500

Characteristic

RAVENOL SU5 ATF Fluid offers:

- Very good lubricity, also by low temperatures in winter
- High, stable viscosity index
- Very good oxidation stability
- Safety against wear, corrosion and foaming
- Excellent friction constant
- High thermal and oxidative stability
- Excellent cooling capacity

| Characteristics | Unit | Data | Audit |
|-----------------|-------------------|------|--------------|
| Colour | | rot | visual |
| Density at 20°C | kg/m ³ | 845 | EN ISO 12185 |
| Pourpoint | °C | -53 | DIN ISO 3016 |

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

02.11.2015

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41