



RAVENOL Schneefräse 4-Takt 5W-30

RAVENOL Schneefräse 4-Takt SAE 5W-30 is high quality fully synthetic green coloured four-stroke engine oil. It is specially designed for 4-stroke snow blowers. Excellent wear protection also by high pressure, excellent corrosion protection. Because of the noticeable fuel economy RAVENOL Schneefräse 4-Takt SAE 5W-30 contributes to the reduction of pollutant emissions and protecting the environment.

Application Notes

RAVENOL Schneefräse 4-Takt SAE 5W-30 is fuel efficient engine oil special conceived for 4-stroke snow blower engines.

Quality Classifications

RAVENOL Schneefräse 4-Takt SAE 0W-30 is tried and tested for aggregates specifying:

Specifications

API SM, API SL, ACEA A5/B5

Practice and tested in aggregates with filling

HONDA, MTD, TORO, Yard-Man, CubCadet, Briggs&Stratton, McCulloch, Craftsman, Murray, Ariens, Caiman, Husqvarna, Partner, Snapper, Stiga, Swisher, White Outdoor, Canadiana

Characteristic

RAVENOL Schneefräse 4-Takt SAE 5W-30 offers:

- Fast oiling of the engine, also by low temperatures
- Low oil consumption because of the low evaporation tendency
- Excellent wear protection by high pressure
- Excellent corrosion protection
- Safety towards sludge, coking, leaking and corrosion also in unfavourable operational conditions
- No oil caused deposits in combustion chambers, in piston ring zone and on valves.
- Neutrality against seal materials

Characteristics	Unit	Data	Audit
Colour		green	visual
Density at 20°C	kg/m ³	850	EN ISO 12185
Viscosity at -30°C	mPa.s	3900	ASTM D5293
Viscosity at 40°C	mm ² /s	55	DIN 51 562
Viscosity at 100°C	mm ² /s	9,9	DIN 51 562
HTHS at 150°C	mPa.s	2,95	CEC-L-36-A-90
Viscosity index VI		170	DIN ISO 2909
Flash point (COC)	°C	230	DIN ISO 2592
Pourpoint	°C	-39	DIN ISO 3016
TBN	mg KOH/g	10	DIN ISO 3771
Sulphated ash	%wt.	1,1	DIN 51 575

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

03.11.2015

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41