



RAVENOL Selfmix 2T

RAVENOL Selfmix 2T is a premixed mineral lubricant which meets the exacting demands of modern two-stroke engines. It effectively prevents the accumulation of carbon deposits in the piston, the combustion chambers and the exhaust ports, and is formulated to avoid contamination of spark plugs and corrosion damage to drive mechanism components.

Application Notes

RAVENOL Selfmix 2T is specially designed for universal use in motorcycles which have separate lubrication and self-mixing systems. When used in separate lubrication systems this product will ensure optimal lubrication and minimizes smoke to help protect the environment. It is suitable for air-cooled as well as water-cooled two-stroke gasoline engines in motorcycles, mopeds and scooters, as well as for other equipment such as lawnmowers etc.

Recommended mixing ratio max. 1:50. - please follow manufacturer's instructions.

As a guide, the contents of a 1 litre pack when mixed will give ratios as follows:

15 liters of fuel = 1: 15 30 liters of fuel = 1: 30

20 liters of fuel = 1: 20 40 liters of fuel = 1: 40

25 liters of fuel = 1: 25 50 liters of fuel = 1: 50

Quality Classifications

Specifications

API TB, ISO-L-EGB, NMMA TC-W

Approvals

JASO FB, Approval JASO 049RAV155

Practice and tested in aggregates with filling

Husqvarna, Stihl, Partner, McCulloch, Jonsered, Oleo-Mac, Poulan, Maruyama, Dolmar, Oregon, Makita, Ryobi, Hitachi

Characteristic

RAVENOL Selfmix 2T offers:

- Excellent corrosion protection
- Excellent oxidation stability
- Very high wear protection
- Environmentally friendly with low smoke formulation
- Low coking capabilities
- Formulated for universal use

Characteristics	Unit	Data	Audit
Colour		rot	visual
Density at 20°C	kg/m ³	872	EN ISO 12185
Viscosity at 40°C	mm ² /s	70,0	DIN 51 562
Viscosity at 100°C	mm ² /s	9,7	DIN 51 562
Viscosity index VI		118	DIN ISO 2909
Flash point (COC)	°C	100	DIN ISO 2592
Pourpoint	°C	-24	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

12.05.2015

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41