



RAVENOL Standard Truck SAE 10W

RAVENOL Standard Truck SAE 10W is mineral mono grade motor oil for trucks. All-season oil for all truck diesel engine types. High protection against friction and abrasion, excellent cold start characteristics. Extended oil change intervals according to manufacturer's recommendations.

Application Notes

RAVENOL Standard Truck SAE 10W is mono grade motor oil for use in truck diesel engines. Also suitable for stationary plants.

Specifications

API SG/CF, ACEA E2/B4

Practice and tested in aggregates with filling

MB 227.0, MB 228.0, MAN 270, Caterpillar TO-2, MTU Type 1, Allison C4, ZF TE-ML 03, 04, 05, 06, 07, 10, 14

Characteristic

RAVENOL Standard Truck SAE 10W offers:

- Good shear stability
- High oxidation stability
- Excellent viscosity temperature behaviour
- Convincing detergent and dispersant characteristics
- High safety reserves
- Good cold start characteristics
- Best corrosion protection
- Suitable for catalysts

| Characteristics | Unit | Data | Audit |
|--------------------|--------------------|-----------|--------------|
| Colour | | gelbbraun | visual |
| Density at 20°C | kg/m ³ | 867 | EN ISO 12185 |
| Viscosity at 40°C | mm ² /s | 36,3 | DIN 51 562 |
| Viscosity at 100°C | mm ² /s | 6,1 | DIN 51 562 |
| Viscosity index VI | | 115 | DIN ISO 2909 |
| Flash point (COC) | °C | 170 | DIN ISO 2592 |
| Pourpoint | °C | -21 | DIN ISO 3016 |

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

04.11.2015

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41