



RAVENOL Super Truck SAE 50

RAVENOL Super Truck SAE 50 is a modern high alloyed HD engine oil with synthetic additives. It is suitable for diesel engines of trucks even with turbo charging.

The high additive content guarantees an excellent effect regarding detergent, dispersant and anti corrosion characteristics.

RAVENOL Super Truck SAE 50 is a top-quality product with high safety reserves.

Application Notes

RAVENOL Super Truck SAE 50 is mono grade motor oil for use in truck diesel engines.

Quality Classifications

Specifications

API CF-4, ACEA E2/B4

Practice and tested in aggregates with filling

MB 228.0

Characteristic

RAVENOL Super Truck SAE 50 offers:

- High oxidation stability
- Excellent viscosity temperature behaviour
- Convincing detergent and dispersant characteristics
- High safety reserves
- Good cold start characteristics
- Best corrosion protection
- Suitable for catalysts
- Reduced emissions

Characteristics	Unit	Data	Audit
Colour		gelbbraun	visual
Density at 20°C	kg/m³	892	EN ISO 12185
Viscosity at 40°C	mm²/s	183,0	DIN 51 562
Viscosity at 100°C	mm²/s	17,5	DIN 51 562
Viscosity index VI		103	DIN ISO 2909
Flash point (COC)	°C	232	DIN ISO 2592
Pourpoint	°C	-18	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

03.11.2015

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41