



RAVENOL TEG 10W-40

RAVENOL TEG 10W-40 is high performance semi-synthetic multi-grade engine oil, based on hydrocrack base oils and PAO, suitable for the lubrication of natural gas engines. It has excellent lubricating film adhesion, very good shear stability and an excellent cleaning power and high resistance to aging.

Application Notes

RAVENOL TEG 10W-40 is suitable to apply as a multi-grade engine oil for natural gas engines.

Quality Classifications

RAVENOL TEG 10W-40 is approved, tried and tested for aggregates specifying:

Specifications

ACEA A3/B4, API SL/CF

Characteristic

RAVENOL TEG 10W-40 offers:

- High wear protection
- Fuel savings through low-friction properties
- Excellent detergent and dispersant properties
- Avoids the formation of accumulations of mud (black sludge)
- Longlife service due to high oxidation stability
- Excellent cold start performance
- Very good viscosity-temperature behavior
- Low evaporation loss

Characteristics	Unit	Data	Audit
Colour		brown	visual
Density at 20°C	kg/m ³	868	EN ISO 12185
Viscosity at 40°C	mm ² /s	91,3	DIN 51 562
Viscosity at 100°C	mm ² /s	14,0	DIN 51 562
Viscosity index VI		157	DIN ISO 2909
Flash point (COC)	°C	200	DIN ISO 2592
Pourpoint	°C	- 35	DIN ISO 3016
TBN	mg KOH/g	7	DIN ISO 3771
Sulphated ash	%wt.	1,5	DIN 51 575

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

02.11.2015

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41